

# RW SIMON Vent-A-Matic Window Ventilators

## Features

### DGS/106

Pullcord Vent-A-Matic with shutters. Controllable ventilator to suit 162mm hole and for Double Glazing up to 32mm thick. Performance Size 9000mm<sup>2</sup>. Complete with Stormguard.

### PBS/DGS

Static Vent-A-Matic, Only 1/8" protuberance. Ideal for open fires, wood burners, boilers and for central heating where continuous ventilation is essential. Suitable for Double Glazing up to 40mm thick.

Fits any circular hole 160mm to 200mm.

Performance Size 10322mm<sup>2</sup>

## Technical Specification

### Exposed Locations

Where the window is in an open aspect or subject to stormy conditions it is recommended that a stormguard is fitted to the unit. These are fitted in seconds.

### Security

If the unit is fitted in an opening light or near to a window handle it is recommended that the unit is secured in place using a clear mastic and a lockable handle is used.

## Ordering Codes

Part Number	Description	Hole Size	Performance	Colour	Box Qty.
VMT30507	DGS 106 Pull Chord with Shutters	162mm	9000mm <sup>2</sup>	Clear	1
VMT30540	DG Stormgaurd Gasboard	160–200mm	10322mm <sup>2</sup>	Clear	1



## Window Ware

Telford Way  
Cross Park  
Bedford  
MK42 0PQ

### Web Site

[www.windowware.co.uk](http://www.windowware.co.uk)

### E-mail

[sales@windowware.co.uk](mailto:sales@windowware.co.uk)

### Sales

**Telephone** 01234 242724

**Fax** 01234 242700/1

### Trade Counter

**Telephone** 01234 242734

**Fax** 01234 242735

### ISO 9001 : 2000

Certificate No. 4010475